

Fimbel Architectural Door Specialties Carriage House Door Design Standards

1. Section Heights – listed from bottom to top
 - a. 6'6" high:26-26-26
 - b. 7'-0" high:26-26-32
 - c. 7'6" high:32-32-26
 - d. 8'0" high:32-32-32

2. Overlay Components –Up to 18'0" wide– all measurements are taken from shoulder
 - a. Bottom Rails: 6 ½"
 - b. Horizontal Rails: 4 ¾"
 - c. Meeting Rails: 2-3/8" x 2 (4 ¾" total)
 - d. Top Rails: 4 ¾" euro: 5 1/8"
 - e. End Stiles: 4 ¾"
 - f. Center Stiles: 9 ½"
 - g. Intermediate Stiles: 3 ½"
 - h. Muntins: 1"
 - i. X-Bucks, V-Bucks, A-Bucks: 3 ½"

3. Overlay Components – Double End Stiles – Over 18'0" wide – all measurements are taken from shoulder
 - a. Bottom Rails: 9"
 - b. End Stiles: 6.25"
 - c. Center Stiles 12.5"
 - d. All other overlays See #2

4. Standard Face Profile Dimensions – all measurements from center
 - a. Simulated V-Groove RT: 5"
 - b. Simulated Beadboard RT: 3.125"
 - c. Mahogany V-Groove: 5.094"
 - d. Mahogany Beadboard: 2.5"
 - e. Cedar V-Groove: 4.813"
 - f. Euro V-Groove: 5"

5. Arch Shoulder Radii – Specified by Top Size- add 4.75" for std opening, 5.125" for euro
 - a. 96 x 26: 147" euro: 146.625"
 - b. 96 x 32: 147" euro: 146.625"
 - c. 108 x 26: 175" euro: 174.625"
 - d. 108 x 32: 147" euro: 146.625"
 - e. 120 x 26: 190" euro: 189.625"
 - f. 120 x 32: 190" euro: 189.625"
 - g. 144 x 26: 300" euro: 299.625"
 - h. 144 x 32: 300" euro: 299.625"

6. Standard Door Thicknesses – by series
 - a. America's Estates: 1 ½"
 - b. Deluxe Estates Paint Grade: 1 ¾"
 - c. Deluxe Estates Stain Grade: 1 ¾"
 - d. All Roaring Twenties: 1 ¾"
 - e. All Early American Series: 2 ¼" (nominal)
 - f. Euro-Dor 1 7/16"

